


**RSA-MFIAQ Multi-function Indoor Air Quality(VOC/CH<sub>2</sub>O/PM2.5/PM10/CO<sub>2</sub>/T/RH) Detector****Applications & Features**

- Simultaneously detect indoor air quality, including multiple VOC, CH<sub>2</sub>O, PM2.5/PM10, CO<sub>2</sub>, T/RH, up to 7 parameters
- VOC: detect various contaminants (VOCs), including wood, paint and others produced by toluene, cigarette, ammonia odor, CO, alcohol, natural gas and even body smell. Low power consumption and good T/RH compensation for high accuracy
- CH<sub>2</sub>O: good accuracy, fast response, excellent anti-interference, extremely low power consumption and good temperature and humidity characteristics, stable and reliable, no need for regular calibration
- PM2.5/PM10: detect the PM2.5 and PM10 concentration in the air with particle sizes 0.3~10µm. The sensor has good long-term stability, high consistency accuracy, real-time response and supports continuous service mode. MBTF is 3+ years for continuous service (service life can be 8-10 years in typical stable concentration change working conditions and auto(intermittent) work mode), free maintenance
- CO<sub>2</sub>: detect the CO<sub>2</sub> concentration of the air with ABC (Automatic Baseline Correction) algorithm, accurate measurement and temperature compensation, good long-term stability and reliability, fast response
- T/RH: use high-precision digital temperature and humidity sensor, ensure good measurement
- Optional red/yellow/green LED indicating the poor/fair/good air quality. The alarm point or interval can be flexibly set through RS485/Modbus
- Power and outputs have over voltage and reverse polarity protection, high reliability and anti-interference capability
- All electrical terminals are on the inside bottom, avoid any possible destroy to PCB when wiring

**Specifications****VOC**

**Sensor:** High performance metal oxide semiconductor sensor, min. 5~7 years life span

**Range:** 0(400) ~2000ppm equivalent CO<sub>2</sub>

**Accuracy:** Typical consistency/accuracy  $\pm 10\%$ FS@25°C

**CH<sub>2</sub>O**

**Sensor:** High performance electrochemical sensor, >3 years life span

**Range:** 0~1000ppb

**Accuracy:**  $\pm 10\%$ FS@25°C

**PM2.5/PM10**

**Sensor:** Laser particulate matter sensor, detected size 0.3~10 µm

**Service Life:** MBTF more than 3 years in continuous service mode, service life up to 8-10 years in auto (intermittent) service mode

**Measuring range:** >1000 µg/m<sup>3</sup>

**Range: PM2.5:** 0~500µg/m<sup>3</sup>, particle size 0.3~2.5µm

**PM10:** 0~600µg/m<sup>3</sup>, particle size 0.3~10µm

**Accuracy:**  $\pm 10$  µg/m<sup>3</sup> @0~100µg/m<sup>3</sup>,  $\pm 10\%$  reading

@100~500µg/m<sup>3</sup>@25°C/50%RH, see accuracy curve

**Resolution:** 1µg/m<sup>3</sup>

**Response time:** in continuous service mode, sample time<1s, general response time<10s

**CO<sub>2</sub>**

**Sensor:** NDIR sensor, with ABC algorithm, >15 years life span

**Accuracy:**  $\pm 50$ ppm $\pm 5\%$  reading @10~40°C

**Response time(T90):** <120s (30cc/min, low airflow)

**Drift:**  $\leq \pm 10$ ppm/year

**Range:** 0~2000ppm (measurement range 400~2000ppm)

**Temperature**

**Sensor:** Digital temperature sensor

**measurement range:** -40~125°C

**Accuracy:** typical  $\leq \pm 1.0$ °C @10~40°C ;  $\leq \pm 1.5$ °C @10~40°C(With CO<sub>2</sub> detection)

**Repeatability:** 0.1°C

**Response time:** typical 10~30s (25°C, low airflow)

**Drift:**  $\leq \pm 0.04$ °C /year

**Relative Humidity**

**Sensor:** Digital capacitance sensor

**Range:** 0~100%RH

**Accuracy:** typical  $\pm 5$  %RH @ 25°C/20~80%RH

**Repeatability:** 0.1%RH

**Hysteresis:**  $\leq \pm 1.0$ %RH

**Response time:** typical 10s (25°C low airflow)

**Drift:**  $\leq \pm 0.25\%$  RH/year

**Power:** 16~28VAC/16~35VDC

**Output:** RS485/Modbus, R/W enable, 9600 bps

**Warm up time:** 15 min

**Working environment:** 0~50°C, 10~90%RH (Non-cond.)

**Storage temperature:** -20~60°C

**Housing:** fire retardant PC (UL94V-0), Protection: IP30

**Weight:** 170-210g

**Approval:** CE

**Models**


Model	RSA-MFIAQ					Multi-function IAQ Detector
VOC		0				N/A VOC detection
CH <sub>2</sub> O			0			N/A CH <sub>2</sub> O detection
PM				0		N/A PM2.5/PM10 detection
CO <sub>2</sub>					0	N/A CO <sub>2</sub> detection
T/RH					1	N/A T/RH detection

For LED indication, add the suffix -LED at the end of the model.

**Note:**

- VOC volatile organic compounds, include over a thousand kinds of component, are widely used in various industries and has great impact on human health, may affect the human liver, kidney, brain and nervous system, resulting in memory loss and other serious consequences, and even cause cancer.
- The VOC sensor could detect varies of VOC components. VOC measurement range 0~1000ppb (isobutene), equivalent to 400~2000ppm of carbon dioxide.
- The CH<sub>2</sub>O sensor could detect only Formaldehyde of 0~1000ppb.
- Exposed to 0.5~1.0 ppm VOC concentration environment have little impact on most people health; exposed to 1.0~10 ppm may have obvious irritation symptoms on human and cancer rates rise 50% to 90%; exposed to above 10 ppm may have serious impact on human health or life threatening.
- China regulations specified the average 8 hours TVOC limit 0.50~0.60 mg/m<sup>3</sup> (equivalent to about 500 ppb) and CH<sub>2</sub>O limit 0.08~0.10 mg/m<sup>3</sup> (equivalent to about 60~75 ppb).
- VOC concentration guidelines and recommendations, mainly refer formaldehyde for reference:

Source	Concentration	Associated Period of Exposure	Health Effect(s)
<b>Based on sensory irritation</b>			
California Environmental Protection Agency (EPA)	44 ppb	1 hour	Eye and airway irritation
Health Canada	100 ppb	1 hour	Eye irritation
National Institute for Occupational Safety and Health	100 ppb	15 minutes	
Occupational Safety and Health administration	750 ppb	8-hour PEL-TWA	Cancer and skin/eye/ respiratory irritation
World Health Organization	81 ppb	30 minutes	Sensory irritation
World Health Organization	100 ppb	short-and long- term	Sensory irritation
<b>Based on respiratory and asthma-like symptoms</b>			
Agency for Toxic Substance and Disease Registry	40 ppb 30 ppb 8 ppb	Daily:1-14 days 15-364 days > 1 year	Respiratory
California EPA	7 ppb 7 ppb	8-hour annual average	Respiratory symptoms Respiratory symptoms
Health Canada	40 ppb (target)	8 hours	Respiratory symptoms in children
<b>Based on cancer risk</b>			
National Institute for Occupational Safety and Health	16 ppb	8 hours	Nasal cancer
Occupational Safety and Health administration	750 ppb	8-hour PEL-TWA	Cancer and skin/eye/ respiratory irritation
World Health Organization	100 ppb	Long-term	Nasal cancer

**PM2.5/PM10 Typical consistency accuracy curve: max deviation (%):**

www.rsa-sensors.com.br  
RSA SENSORES, CONTROLES,  
VALVULAS, ATUADORES E  
EQUIPAMENTOS

RSA SENSORES - ATENDIMENTO



ESCANEAR O QR CODE COM CAMERA DO  
CELULAR, PARA CHAMAR NO WHATS APP  
SAC: (11)979936574